



# EDSON ELECTRONICS

## AQUALIFE EP SEALER – TECHNICAL DATA Water-Based Primer

A two pack water based epoxy sealer/surface stabiliser for bare concrete floors.

Aqualife is a modified epoxy resin cured with a water dispersible amine, diluted with water for application.

### **Physical Properties:**

Volume Solids:	Approx 30%
Typical Thickness:	30 microns per coat
Appearance:	Clear
VOC Content:	Below 25gms/litre
Drying @ 20C:	Touch Dry 4 Hrs Hard Dry 16 Hrs Full Cure 7 Days
Pot Life:	6-8 Hrs at 20C
Coverage:	10m sq/Litre
Mix Ratio:	Base/Activator supplied in correct ratio
Method of Application:	Brush, roller or airless spray
Cleaner:	Water
Storage & Handling:	Protect from Frost. Keep out of reach of children
Pack Size:	5 Litres
Flash Point:	Non Flammable
Product Weight:	1.04kg/litre
Shelf Life:	2 years
Limitations:	Do not apply if the temperature is below 10C The use of hot air blowers is recommended if the temp falls below 15C Curing times are dependent on temperature, humidity and ventilation
Preparation:	Surface should be clean, dry ( <b>below 5.5 on protimeter scale if new concrete</b> ) and free from surface contamination Existing coatings should be removed