



Automatic Unloader FU-300CE

FEATURES

- Safety design
- Remove a magazine shaking with side clamping type
- Various feeding pitch (1~4) steps (10, 20, 30, 40 mm)
- Contribute to stable quality and productivity elevation
- Easy operation panel
- Magazine change overtime (20 seconds)
- Automatic conveyor width & pusher position adjustment
- Universal & SMEMA Interface
- CE model (CE-type)

SPECIFICATIONS

MODEL/ SPECIFICATIONS	FU-300CE	FU-300S,L,CE	FU-300S,LL,CE	FU-300S,XL,CE
No OF MAGAZINES	3rack, upper:1, lower:2			
P.C.B SIZE mm	50×50 250×330 0.5~2.0 t	70x70 330x440 0.5~2.0 t	50x50 390x510 0.5~2.0 t	50x50 460x510 0.5~2.0 t
MAGAZINE SIZE (WxLxH) mm	320x355x570	320x355x570 400x460x570	320x355x570 460x535x570	320x355x570 530x535x563
DIMENSION (WxLxH) mm	860x1925x1750	920x2190x1750	990x2515x1750	1060x2515x1750
POWER SUPPLY	AC110/220V 50/60Hz (0.4KVA)			
AIR	5~7 Kgf/cm ²			
WEIGHT	210 Kg	250 Kg	280 Kg	320 Kg